

1.0m Maritime Automatic Flyaway Antenna

Product Category : Iridium and Maritime Truraya



Product Parameters

Antenna Category	Iridium and Maritime Truraya
Antenna Aperture	1.0m
Antenna Type	Feed back
Polarization	Linear
Frequency (Rx)	1.525-1.559GHz
Frequency (Tx)	1.626-1.660GHz

Port isolation (Rx-Tx)	≥ 85 dB
Port isolation (Tx-Rx)	≥ 40 dB
Gain(Rx)	$\geq 20.1 + 20\lg(f/1.525)$ dB <i>i</i>
Gain(Tx)	$\geq 20.64 + 20\lg(f/1.626)$ dB <i>i</i>
VSWR(Rx)	$\leq 1.5:1$
VSWR(Tx)	$\leq 1.5:1$
Motion range (AZ)	$\pm 180^\circ$
Motion range (EL)	$10^\circ \sim 90^\circ$
Motion range (POL)	$\pm 90^\circ$
AZ	$0.1 \sim 3^\circ/s$
EL	$0.1 \sim 3^\circ/s$
POL	$0.1 \sim 3^\circ/s$
Initial acquisition time	≤ 3 min
Blockage recovery time	≤ 1 min
Power capacity	≤ 500 W
Operating Temperature	$-40^\circ\text{C} \sim +60^\circ\text{C}$
Storage Temperature	$-55^\circ\text{C} \sim +70^\circ\text{C}$
Humidity Requirement	95%(20°C)
Operating wind velocity	13m/s
Survival wind velocity	20m/s
Protection grade/IP Rating	IP65
Power supply	90~264VAC,47Hz~63Hz
power consumption	≤ 350 W(No power amplifier)
Material	Other Materials
Remarks	

Contact Us

Phone:(86)029-81156153

Email:bxg0@sohu.com

Web:<http://localhost/>

Address:9th Floor, No. 32 Chuanghui Road, High-tech Zone, Xi'an City, Shaanxi Province, China