

Martime/Truraya Drive away Antenna

Product Category : Drive Away



Product Parameters

Antenna Category	Drive Away
Antenna Aperture	
Antenna Type	
Polarization	Dual Circular
Frequency (Rx)	1518.00MHz-1675.00MHz
Frequency (Tx)	1518.00-1675.00MHz
Port isolation (Rx-Tx)	

Port isolation (Tx-Rx)	
Gain(Rx)	
Gain(Tx)	
VSWR(Rx)	
VSWR(Tx)	
Motion range (AZ)	±180°
Motion range (EL)	10°~90°
Motion range (POL)	
AZ	0.1~3°/s
EL	0.1~1°/s
POL	
Initial acquisition time	
Blockage recovery time	
Power capacity	
Operating Temperature	-40°C ~ +60 °C
Storage Temperature	-55°C ~ +70 °C
Humidity Requirement	
Operating wind velocity	
Survival wind velocity	
Protection grade/IP Rating	
Power supply	90~264VAC,47Hz~63Hz
power consumption	
Material	Carbon Fiber
Remarks	

Contact Us

Phone:(86)029-81156153

Email:bxg0@sohu.com

Web:http://localhost/

Address:9th Floor, No. 32 Chuanghui Road, High-tech Zone, Xi'an City, Shaanxi Province, China