

# 0.8m Low Profile On The Move Antenna

Product Category : Drive Away



## Product Parameters

<b>Antenna Category</b>	Drive Away
<b>Antenna Aperture</b>	0.8m
<b>Antenna Type</b>	Feed back
<b>Polarization</b>	Linear
<b>Frequency (Rx)</b>	10.70-12.75GHz
<b>Frequency (Tx)</b>	13.75-14.50GHz
<b>Port isolation (Rx-Tx)</b>	

<b>Port isolation (Tx-Rx)</b>	
<b>Gain(Rx)</b>	$\geq 34.89 + 20\lg(f/12.50)\text{dBi}$
<b>Gain(Tx)</b>	$\geq 36.03 + 20\lg(f/14.25)\text{dBi}$
<b>VSWR(Rx)</b>	$\leq 1.5:1$
<b>VSWR(Tx)</b>	$\leq 1.5:1$
<b>Motion range (AZ)</b>	360° Continuous Unlimited Rotation
<b>Motion range (EL)</b>	0°~90°
<b>Motion range (POL)</b>	$\pm 90^\circ$
<b>AZ</b>	
<b>EL</b>	
<b>POL</b>	
<b>Initial acquisition time</b>	Initial Acquisition Time Static: $\leq 80\text{S}$ , Dynamic: $\leq 120\text{s}$ , Shadowing
<b>Blockage recovery time</b>	Initial Acquisition Time Static: $\leq 80\text{S}$ , Dynamic: $\leq 120\text{s}$ , Shadowing
<b>Power capacity</b>	
<b>Operating Temperature</b>	-40°C ~ +60 °C
<b>Storage Temperature</b>	-55°C ~ +70 °C
<b>Humidity Requirement</b>	
<b>Operating wind velocity</b>	
<b>Survival wind velocity</b>	
<b>Protection grade/IP Rating</b>	IP65
<b>Power supply</b>	90~264VAC,47Hz~63Hz
<b>power consumption</b>	
<b>Material</b>	Carbon Fiber
<b>Remarks</b>	

## Contact Us

Phone:(86)029-81156153

Email:bxg0@sohu.com

Web:<http://localhost/>

Address:9th Floor, No. 32 Chuanghui Road, High-tech Zone, Xi'an City, Shaanxi Province, China