

# Iridium Antenna

Product Category : Iridium and Maritime Truraya



## Product Parameters

<b>Antenna Category</b>	Iridium and Maritime Truraya
<b>Antenna Aperture</b>	
<b>Antenna Type</b>	
<b>Polarization</b>	Circular
<b>Frequency (Rx)</b>	1616-1626.5MHz
<b>Frequency (Tx)</b>	1616-1626.5MHz
<b>Port isolation (Rx-Tx)</b>	

<b>Port isolation (Tx-Rx)</b>	
<b>Gain(Rx)</b>	≥3.0dBi
<b>Gain(Tx)</b>	≥3.0dBi
<b>VSWR(Rx)</b>	≤2.0:1
<b>VSWR(Tx)</b>	≤2.0:1
<b>Motion range (AZ)</b>	
<b>Motion range (EL)</b>	
<b>Motion range (POL)</b>	
<b>AZ</b>	
<b>EL</b>	
<b>POL</b>	
<b>Initial acquisition time</b>	
<b>Blockage recovery time</b>	
<b>Power capacity</b>	
<b>Operating Temperature</b>	-40°C ~ +60 °C
<b>Storage Temperature</b>	-55°C ~ +70 °C
<b>Humidity Requirement</b>	
<b>Operating wind velocity</b>	
<b>Survival wind velocity</b>	
<b>Protection grade/IP Rating</b>	IP65
<b>Power supply</b>	
<b>power consumption</b>	
<b>Material</b>	Other Materials
<b>Remarks</b>	Interface N-50K configuration LNA, Tripod

## Contact Us

Phone:(86)029-81156153

Email:bxg0@sohu.com

Web:http://localhost/

Address:9th Floor, No. 32 Chuanghui Road, High-tech Zone, Xi'an City, Shaanxi Province, China