

Maritime Truraya Antenna

Product Category : Iridium and Maritime Truraya



Product Parameters

Antenna Category	Iridium and Maritime Truraya
Antenna Aperture	
Antenna Type	
Polarization	Dual Circular
Frequency (Rx)	1518.00MHz-1675.00MHz
Frequency (Tx)	1518.00-1675.00MHz
Port isolation (Rx-Tx)	

Port isolation (Tx-Rx)	
Gain(Rx)	≥18.0dBi
Gain(Tx)	≥18.0dBi
VSWR(Rx)	≤2.0:1
VSWR(Tx)	≤2.0:1
Motion range (AZ)	
Motion range (EL)	
Motion range (POL)	
AZ	
EL	
POL	
Initial acquisition time	
Blockage recovery time	
Power capacity	
Operating Temperature	-40℃ ~ +60 °C
Storage Temperature	-55℃ ~ +70 °C
Humidity Requirement	
Operating wind velocity	
Survival wind velocity	
Protection grade/IP Rating	IP65
Power supply	
power consumption	
Material	Other Materials
Remarks	Interface N-50K

Contact Us

Phone:(86)029-81156153

Email:bxg0@sohu.com

Web:<https://www.nebulasignal.com/>

Address:9th Floor, No. 32 Chuanghui Road, High-tech Zone, Xi'an City, Shaanxi Province, China