

Logarithmic periodic antenna

Product Category : Manual Flyaway



Product Parameters

Antenna Category	Manual Flyaway
Antenna Aperture	
Antenna Type	
Polarization	Linear
Frequency (Rx)	30-3000MHz
Frequency (Tx)	30-3000MHz
Port isolation (Rx-Tx)	

Port isolation (Tx-Rx)	
Gain(Rx)	≥6.5dBi
Gain(Tx)	≥6.5dBi
VSWR(Rx)	≤2.0:1
VSWR(Tx)	≤2.0:1
Motion range (AZ)	
Motion range (EL)	
Motion range (POL)	
AZ	
EL	
POL	
Initial acquisition time	≤3min
Blockage recovery time	≤1min
Power capacity	
Operating Temperature	-40°C ~ +60 °C
Storage Temperature	-55°C ~ +70 °C
Humidity Requirement	
Operating wind velocity	
Survival wind velocity	
Protection grade/IP Rating	IP65
Power supply	
power consumption	
Material	Carbon Fiber
Remarks	Model Number:NBT-ZT07B Interface N-50K

Contact Us

Phone:(86)029-81156153

Email:bxg0@sohu.com

Web:http://localhost/

Address:9th Floor, No. 32 Chuanghui Road, High-tech Zone, Xi'an City, Shaanxi Province, China